



15-5F, No.738,
Jhongheng Rd., Jhonghe
City, Taipei County, 235,
Taiwan, R.O.C
TEL:+886-2-82261676
FAX:+886-2-82261620
www.jstac.com

Media Module

Dimensions: 114 x 60 x 7 mm

Weight: Approximately 10g



- Input memory Card Interface.
(Support CF /Micro-drive /SM /SD /MMC /MS /MS PRO card.)
- Supports image format: JPG.
- Supports audio format: MP3.
- Supports: video format: MPEG1, MPEG2, MPEG4 (Till DIVX 5.1.1); Motion JPEG.
- Watching JEPG, AVI, MP3, MPEG1, MPEG2, MPEG4; Motion JPEG formats at screen from different kind of Memory cards by Remote controller.
- Non PC operations only need to connect with screen then you can watch movies, listen music by remote controller easily.
- Special images slide show MP3 background music supported.
- Provides several image display functions: Slide Show, Auto Slide Show, Preview, Zoom, Rotate, and so on.
- Supports still picture resolution up to 7M pixels.
- Supports Resolution by 720 X 480 30 frame/NTSC, 720X576 (25 frame/PAL).
- Supports thumbnail pictures decompression.
- JPEG decoder Output by 4:2:2.
- Multiple languages OSD supported. (Chinese traditional / simplified & English)
- English/Chinese (Japanese/English) files name supported.
- Firmware upgradeable from memory card.

- Support Audio format LPCM, ADPCM(48K~96K),not support AC3,ACC format.
- Composite & VGA out put interface.(Video, Audio-L/R)

Power Supply

Application: 12V/DC